



Model

FS105D

5-Port 10/100Mbps
Desktop Switch



Up to 200Mbps



Plug & Play



Power Saving

[Datasheet](#)

Features

- Comply with IEEE802.3, IEEE802.3i, IEEE 802.3u, IEEE802.3x, IEEE802.3az Ethernet standards.
- Support 5 x10/100Mbps Auto-negotiation RJ45 ports, support auto MDI/MDIX.
- Support IEEE802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode.
- Supports IEEE802.3az energy efficient ethernet (EEE) technology.
- 1K entry MAC address table of the switch with auto-learning and auto-aging.
- LED indicators for monitoring Port Link/Activity.
- External power supply, exquisite plastic design, suitable for desktop install and use.

Specifications

Model Name	FS105D	
Chipset	IP178G	
Standards and Protocols	IEEE802.3, IEEE802.3i, IEEE 802.3u, IEEE802.3x, IEEE802.3az	
Interface	5 x 10/100Mbps Auto-Negotiation ports	
Network Media	10Base-T: UTP category 3, 4, 5 cable (maximum 100m)	
	100Base-Tx: UTP category 5, 5e cable (maximum 100m)	
Transfer Method	Store-and-Forward	
MAC Address Table	1K	
Switching Capacity	1Gbps	
Packet Forwarding Rate	744Kpps	
Indicators	Per Device	Power
	Per Port	Link/Activity
Power Supply	DC: 5V, 0.5A External Power	
Power Consumption	Maximum: 1.3W (220V/50Hz)	
Dimensions (W x D x H)	88.2 * 52.7 * 21.8mm	
Environment	Operating Temperature: 0°C~45°C	
	Storage Temperature: -40°C~70°C	
	Operating Humidity: 10%~90% non-condensing	
	Storage humidity: 5%~90% non-condensing	

