



UT133B

Specifications	Range	UT133A	UT133B
Certificates	CE, UKCA, cETLus		
DC voltage (V)	600mV/6000mV/60V/600V	±(0.7%+3)	±(0.7%+3)
AC voltage (V)	600V	±(0.7%+3)	±(1.2%+3)
DC current (A)	600μA/60mA/600mA/10A	±(1%+3)	±(1%+2)
AC current (A)	10A	±(1.2%+3)	
Resistance (Ω)	600Ω/6000Ω/60kΩ/600kΩ/60MΩ	±(0.8%+2)	±(0.8%+2)
Capacitance (F)	9.999mF	±(4%+5)	±(4%+5)
Frequency (Hz)	10.00Hz~1.000MHz	±(0.1%+5)	
Temperature (°C)	-40°C~1000°C	±(1%+4)	
Temperature (°F)	-40°F~1832°F	±(1.5%+5)	
Display count		6000	6000
Range selection		Auto	Manual
Battery test	Tests 1.5V and 9V batteries and displays 'good', 'low', 'bad' status		v
Category ratings	CAT III 600V		

Features	
Over voltage/current audible alarm	Continuity buzzer
High voltage warning	NCV
Auto power off (can be disabled)	LCD backlight
Low power consumption	Test probe holder
Battery test with status	Data hold
Diode	Low battery indication
2m drop proof	Overload indication

Characteristics	
Standard accessories	Test leads, K-type thermocouple (UT133A), English manual
Power	1.5V battery (R03) x 2
Display	50 x 23mm
Product size	155 x 76.5 x 49mm
Product net weight	255g (with batteries)
Standard individual packing	Gift box
Standard quantity per carton	30pcs
Standard carton measurement	350 x 335 x 318mm
Standard carton gross weight	11.8kg

